



MAIN FEATURES

- •Impressive sound pressure
- •Real time monitoring via RDNet protocol
- •FIR Filters
- •Front-fill use
- Wall-mountable
- Suitable for installation
- •Ultra light-weight

DESCRIPTION

The powerful and detailed sound of VIO X family into a small, ultraperforming cabinet: ideal as front-fill or under balcony in large VIO sound reinforcement systems and perfect for vertical or horizontal fixed installation.

VIO X205 fits any project as full-range PA, fixed installation, FOH monitoring, front-fill in large sound reinforcement systems, and more.

This solid wooden cabinet is reinforced with a polyurea finish and features M10 threaded nuts on top and bottom allowing installation with accessories WB-VIOX205 H (horizontal bracket) or WB-VIOX205 V (vertical bracket). The cabinet can be easily installed on pole thanks to SA-VIOX205 pole mount adaptor (35mm) allowing 2 tilt options.

ACCESSORIES



WB-VIOX205V Vertical bracket for VIO X205




WB-VIOX205H Horizontal bracket for VIO X205



Speaker stand adapter for VIO X205

SA-VIOX205



Speaker Type	2 Way Active Loudspeaker
Frequency Response [-10dB]	75 - 21.000 Hz
Max SPL (1 m)	126 dB
Directivity X205-60	60° x 60°
Directivity X205-100	100° x 100°
HF	1x 1", 1.4 v.c.
LF	2x 5", 1" v.c
Amplifier	400 W RMS Class-D Digipro® G3
Power Supply	Auto-range SMPS
Limiter	Peak, RMS, Thermal
Processing	FIR Linear Phase Filters
Controller	28/56 bit DSP
AD/DA Converter	24 bit/48 kHz
Controls	1x Rotary Encoder (8x EQ presets) 1x Input Attenuation Rotary Switch 1x On LED 1x Status LED 1x Signal LED 1x Limiter LED
Signal Input	1 x XLR balanced, 1 x RJ45 Link (RD- Net), 1x USB (Data Service)
Signal Output	1x XLR balanced, 1 x RJ45 Link (RD-Net)
Housing	Wooden Cabinet, Polyurea painting
Wedge Angle	5° Monitor use
Rigging Points	2x M10 Threaded Nuts (top and bottom)
Width	150 mm (5.9 in)
Height	485 mm (19 in)
Depth	240 mm (9.4 in)
Weight	7.8 kg (17.2 lbs)



FC-VIOX205

Functional cover for VIO X205